

Nikon COOLPIX L12

Digital Camera Specifications

Type:	Compact digital camera
Product name:	COOLPIX L12
Effective pixels:	7.1 million
CCD:	1/2.5 inch-type interline CCD; total pixels: approx. 7.41 million
Image Modes:	7M High (3072 x 2304)/Fine, 7M Normal (3072 x 2304)/Normal, 3M Normal (2048 x 1536)/Normal, PC Screen (1024 x 768)/Normal, TV screen (640 x 480)/Normal, 16:9 (3072 x 1728)/Normal
Lens:	3x Zoom-Nikkor; 5.7-17.1mm (35mm [135] format picture angle: 35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: approx. 420mm)
Focus range (from lens):	50cm (1 ft. 8 in.) to infinity (∞), Macro close-up mode: 15cm (5.9 in.) to infinity (∞)
Vibration Reduction (VR):	Optical Lens shift VR
ISO sensitivity	Auto (auto gain ISO 50-1600)
LCD Monitor:	2.5 inch-type, 115,000-dot, TFT LCD with anti-reflection coating
Storage media:	Internal memory (approx. 21 MB) and SD memory cards
Shooting modes:	Auto, 15 Scene modes ((Face-priority AF, Portrait, Landscape, Sports, Night Portrait, Party/indoor, Beach/Snow, Sunset, Dusk/Dawn, Night Landscape, Close up, Museum, Fireworks show, Copy, Back Light, Panorama Assist), Voice recording, BSS (Best Shot Selector), Color Options, Blur Warning, Date Imprint
Movie:	With sound: TV movie (640) at 30fps, Small size (320) at 30fps/15fps, Smaller size (160) at 15fps, Streaming, Stop-motion movie

Capture Modes:	1) Single, 2) Multi-shot 16 (approx. 1.6 fps.)
Built-in flash:	Range: 1 ft. 8 in. – 26 ft. 3 in./ 0.5-8.0m (W), 1 ft. 8 in. – 14 ft. 9 in./ approx. 0.5-4.5m (T); Flash modes: Auto, Auto with red-eye reduction (In-Camera Red-Eye Fix), Anytime flash, Flash cancel, and Slow sync
Interface:	USB, Audio Video
Supported Languages:	Czech, Danish, German, English, Spanish, French, Indonesian, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Finnish, Swedish, Chinese (Simplified and Traditional), Japanese, Korean, Thai
Power requirement:	Two AA alkaline, oxyride, or lithium batteries, two EN-MH1 rechargeable NiMH batteries (optional), EH-65A AC adapter (optional)
Battery life (approx):	150 shots with alkaline, 600 shots with lithium, or 370 shots with EN-MH1 batteries (based on CIPA standard)
Dimensions (WxHxD):	91 x 61 x 26 mm (3.6 x 2.4 x 1.0 in.) excluding projections
Weight:	Approx. 4.4 oz. (125g) without battery and SD memory card
Supplied Accessories*:	Two 1.5V LR6 AA-size alkaline batteries, USB Cable UC-E6, Audio Video Cable EG-CP14, Strap, Dock Insert PV-13, PictureProject CD-ROM
Optional Accessories:	Battery Charger MH-71, Ni-MH Rechargeable Battery EN-MH1, AC Adapter EH-65A
	* Supplied accessories may differ by country or area.

PictureProject System Requirements

OS

Macintosh: Mac[®] OS X version 10.3.9, 10.4.x

Windows: Windows[®] Vista (32bit), Windows[®] XP Home Edition/Professional, Windows[®] 2000 Professional pre-installed models

Note

CD-ROM drive required for installation. Only built-in USB ports are supported.

Microsoft[®] and Windows[®] are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh[®] and QuickTime[®] are either registered trademarks or trademarks of Apple Computer Inc. in the United

States and/or other countries. The SDHC logo is a trademark. ImageLink and the ImageLink print system logo are trademarks of Eastman Kodak Company. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. February 2007 ©2007 NIKON CORPORATION